

PS20



CE 0425 CE 0474 MDR

Professional electronic patient lift dynamometer



- PS-20 is a versatile and universal solution
- Thanks to the movable rings, installation is easy and immediate
- The compact structure makes the instrument easier to transport
- Hooks and rings allow simple and safe use

WU150 - Standard

Weight, tare, hold, BMI (body mass index), auto zero, programmable auto-off

Certifications

NAWI metric directive 90/384-2014/31/EU

Precision class III according to EN45501 standards

Medical devices MDR Regulation (EU) 2017/745

Risk class Im with measuring function

Structure

Painted tubular structure with ABS display

Single cell load weighing system

Dimensions

W530 x D120 x H340 mm

Power supply

External power supply and alkaline battery holder 6 x AAA (batteries not included) or 40h rechargeable battery kit (optional)

Variable opening width

Thanks to the orientating rings, PS-20 is compatible with a wide range of structures and patient lifts, up to a maximum opening of 530 mm




Maximum opening: 530 mm



Minimum opening: 275 mm

Versatile use



Standard hook



PS20 - Single hook



PS20 A - Double snap hook

PS-20 offers the versatility of 3 “hanging” solutions for patient lift harnesses. The standard option allows coupling of simple harnesses directly on the structure. By applying the snap hooks, more complex harnesses can be used that require multiple coupling points. Version **PS20 A** is equipped with 4 snap hooks, 2 for each side of the hanging scale.

GMDN: 35996

Model	Code	Capacity	Division
PS20	M35 120	200 kg	100 g
PS20 A	M35 121		

Price on request to info@liden-weighing.se

Accessories included: adapter, RS232, level, 2 years warranty. Snap hook only with model PS20 A

Optionals	Code
Software wMed Basic	M35 920
Rechargeable batteries 40h run time	M35 900
WS thermal printer	M35 921
Bluetooth	M35 910
Wifi	M35 911

